

EBS-4U500

19" Rackmount 4U SYSTEM/BAREBONE, applicable to various industries widely.

Features

- Industrial-grade design for stable operation even in harsh environments
- Superb resilience to electromagnetic interference
- Hard drive bay can support 1*5.25" and 3*3.5"
- Excellent expansibility with 7 Full Height PCI/PCIe Expansion Slots
- With 1.2mm durable SGCC & SPCC sheet metal
- Embedded with trusted industrial power supply for reliability
- Low-noise, ball-bearing fan for better thermal performance




Specifications

Drive Bay	Storage	1*5.25" +3*3.5"(or 5*2.5")
Front I/O	USB2.0	2
Switch		1 x Power on/off, 1 x System Reset
Expansion Slot		7 slots, Full Height PCI/PCIe Expansion Slots
Indicators	LED Indicators	Power LED, Reset LED
Cooling		1 x 12025 Fan with Silent bearing
Power Supply	Wattage	ATX PSU up to 1300W, or Mini-redundant 500W
Environment	Operating Temperature	0~40°C
	Non-Operating Temperature	-15~60°C
	Relative Humidity	10~95%@40°C, non-condensing
Physical Characteristics	Steel plate thickness of chassis	1.2mm SGCC & SPCC
	Dimension	430.0x457.7x175.7mm(WO/Handle), 483x507.85x175.7mm(W/Handle)
Certification	EMI & Safety	Pre-test 、 CE

Rear I/O & Internal Connector

Rear I/O	Standrad motherboard I/O shield	Refer to the configuration of selected motherboard (ATX, micro ITX or Mini-ITX)
-----------------	---------------------------------	---------------------------------------------------------------------------------

Front View




- 2 x USB 2.0
- 1 x Power Status LED
- 1 x Hdd LED
- 1 x Power On/Off
- 1 x System Reset

Back View



- 7 x Expansion Slots
- 1 x Stand IO area for MB
- 2 x 6025 Fan Holes
- 6 x Knockout Ports of Com
- 1 x Knockout Port of Parallel port
- 1 x Knockout Port of Remote power

Dimension



Ordering Information

Model name	Part number	Description
EBS-4U500	90AE02D*	EBS-4U500

* The part number might vary for different regulations and package. Please consult the TPM in your region for exact 90PN.

Packing List

Part number	Description	Quantity
14009*	AC POWER CORD	1 (optional)
13AE0*	SYSTEM ACCESSIOR	1
14013*	SATA 6G CABLE (Barebone sku only)	1
13020*	M.2 SCREW PACK (Barebone sku only)	1

* The handle is not assembled by default for transport safety, and the part number might vary due to part number revision.