

# ASUS BE248CFN

## Docking Monitor



Accessory slot for phone holder

PC mounted via mini PC kit

## Key Features



Optimized for the finest image and color quality with 178° wide-viewing-angle



100Hz refresh rate gives you so much more on top of the best smooth and quality for any content



DisplayPort

Extensive connectivity of USB-C, HDMI, DP in, DP out for daisy chain, USB hub and earphone jack



Daisy-chain

DisplayPort allows users to daisy chain for a multi-display setup from one video source.



USB Hub

Embedded USB3.2 hub (4 ports) for connecting mouse, keyboard, or other USB devices



USB Type-C

Full function USB-C connection for DisplayPort video, USB data transmission and supports up to 96W power delivery



RJ-45

Delivers stable Internet connection and one-cable docking to your laptop with RJ45 and USB-C connection



4-way Ergonomic Stand

Ergonomically-designed stand with tilt, swivel (+180° ~ -180°), pivot, and height adjustments



Wall Mountable

Space saving from compatible VESA mount standard (100 x 100 mm) and bundled ASUS miniPC kit(optional)



(By country)



The mark of responsible forestry



# Specification

Display	Panel Size(diagonal)	24.1"(61.13 cm) Wide Screen (16:10)
	Display Viewing Area(HxV)	518.4 x 324.0 mm
	Panel Type	IPS
	Display Surface	non-glare
	Color Saturation	100% sRGB
	True Resolution	1920x1200
	Pixel Pitch	0.270mm
	Brightness (Max.)	350cd/m <sup>2</sup>
	Contrast Ratio (Max.)	3000:1
	Viewing Angle (CR ≥ 10)	178°(H)/178°(V)
	Display Colors	16.7 million
	Response Time	5ms (GTG)
	Refresh Rate (Max)	100Hz
	Flicker-free	Yes
Features	Splendid™ Video Intelligence Tech.	Yes
	Color Temperature Selection	4 modes (Cool/Normal/Warm/User)
	HDCP support	Yes (ver. 1.4)
	QuickFit	Yes
	Blue Light Filter	Yes
	VRR Technology	Yes (Adaptive-Sync)
	DisplayWidget	Yes, DisplayWidget Center
Audio		Stereo Speaker 1W x 2
Input/ Output		USB-C DP Alt mode with PD 96W, HDMI, DP, DP output(for daisy-chain), USB3.2 Gen1 x4 ports (downstream), Earphone jack , RJ45
Signal Frequency	Digital Signal Frequency	30~130 KHz (H) / 48~100 Hz (V)
Power	Power Consumption*1	14.85W
	Power Saving Mode	<0.5W
	Power Off Mode	0W(hard switch)
	Voltage	100-240V, 50 / 60 Hz
Mechanical Design	Color	Black
	Tilt(angle)	Yes (+35° ~ -5°)
	Swivel(angle)	Yes (+180° ~ -180°)
	Pivot(angle/direction)	Yes (+90° ~ -90°)
	Height Adjustment	Yes (0~130mm)
VESA Wall Mounting	100x100mm	
Security	Kensington lock	Yes
Dimension	Phys. Dimension (WxHxD)	53.18 x 47.31x 21.12 cm (20.94" x 18.63" x 8.31")(highest with stand) 53.18 x 34.31x 21.12 cm (20.94" x 13.51" x 8.31")(lowest with stand) 53.18 x 35.00 x 4.00 cm (20.94" x 13.78" x 1.57")(without stand)
	Box Dimension (WxHxD)	61.0 x 41.4 x 14.00 cm (24.02" x 16.30" x 5.51")
Weight		Net Weight : 5.8 kg (12.79 lbs) Net Weight without Stand : 4.05 kg (8.93 lbs) Gross Weight : 8.5 kg (18.74 lbs)
Accessories(vary by regions)		Power cord(1.8m), HDMI cable(1.8m), USB-C cable(1.5m), DisplayPort Cable(optional), Warranty card, Quick Start Guide, mini PC kit(optional)
Compliance Standards		Energy Star, FCC, cTUVus., ICES-3, CB, CE, ErP, WEEE, TUV-GS, TUV-Ergo, ISO 9241-307, CU, CCC, CEL, AU MEPS, VCCI, PSE, J-MOSS, KC, KCC, e-Standby, CEC, TCO, RoHS, WHQL Windows 10/11, EPEAT Gold(by country), TUV Flicker free, TUV Low Blue Light

\*1. Measuring a screen brightness of 200 nits without audio/ USB/ Card reader connection

\*.All specifications are subject to change without notice.