



Engineered for Business and Commercial Needs













ASUS NUC 12 Pro Mini PCs, Kits, and Boards raise the bar for performance and connectivity in a 4x4 device for productivity, collaboration, and edge compute. 12th Gen Intel® Core<sup>TM</sup> processors—plus up to 64GB dual-channel memory and massive SSD capacity—drive enterprise-class performance in a pint-sized PC. Select ASUS NUC 12 Pro SKUs feature Intel vPro® Enterprise for Windows with 12th Gen Intel® Core<sup>TM</sup> processors, which provides performance, security, stability, and manageability features for managed businesses of all sizes.

#### **Key Selling Points**

**Powerful Performance Perfect Fit**: Experience the advanced power and performance for edge computing, collaboration, home offices, and more—12th Gen Intel® Core™ processors deliver it all.

**Small Size. Big Business Performance**: ASUS NUC 12 Pro sets new standards with 12th Gen Intel® Core<sup>TM</sup> processors, up to 64 GB dual-channel memory, ample SSD capacity, and lightning-fast connectivity in a compact 4x4 design.

**The Power of Small**: With a  $4" \times 4"$  footprint, pint-sized NUC 12 Pro Mini PCs and Kits are available in two chassis, including tall kits with a 2.5" drive bay and an internal expansion bay.

**Brilliant graphics**: Small size and brilliant graphics technologies make NUC systems an ideal choice for kiosks, signage, video walls, and more. Choose from systems with Intel<sup>®</sup> Iris<sup>®</sup> X<sup>e</sup> graphics or customizable discrete graphics.

#### **Audience**

- Office Productivity
- Digital Signage / Kiosk Embedded
- Collaboration
- Surveillance / Edge Compute









Image A

Image B

Mini-PC Specifi	cations	Image A Image B
Marketing Name	ASUS NUC 12 Pro Mini-PC	ASUS NUC 12 Pro Mini-PC
Project Code	NUC12WSH	NUC12WSK
Photo	Image A	Image B
ASUS Logo	-	-
ASUS NUC Logo	N/A	N/A
	N/A	N/A
Color	Black	Black
OS Support	Windows 11 64-bit	Windows 11 Pro 64-bit
CPU	Intel® Core™ i7-1260P Processor, cTDP 40W Intel® Core™ i5-1240P Processor, cTDP 40W Intel® Core™ i5-1220P Processor, cTDP 40W	Intel® Core™ i7-1260P Processor, cTDP 40W Intel® Core™ i5-1240P Processor, cTDP 40W Intel® Core™ i5-1220P Processor, cTDP 40W
Chipset	Integrated	Integrated
Graphics	Intel® Iris® Xe Graphics (i5/i7) Intel® UHD Graphics (i3)	Intel® Iris® Xe Graphics (i5/i7) Intel® UHD Graphics (i3)
Memory	2 x SO-DIMM, Up to DDR4-3200, 32GB*2	2 x SO-DIMM, Up to DDR4-3200, 32GB*2
Storage	1 x M.2 2280 PCle Gen4x4, supports 128GB~8TB NVMe SSD 1 x M.2 2242 PCle x1, supports SATA 128GB~1TB SATA SSD 1 x 2.5" SATA 6Gb/s, supports 4TB 7~15mm HDD	1 x M.2 2280 PCIe Gen4x4, supports 128GB~8TB NVMe SSD 1 x M.2 2242 PCIe x1, supports SATA 128GB~1TB SATA SSD 1 x SATA Power/DATA header for 2.5in SSD/HDD, supports 128GB~2TB SATA drive
Wireless Network	Intel® AX211 (Gig+), Wi-Fi 6E, Bluetooth 5.3	Intel® AX211 (Gig+), Wi-Fi 6E, Bluetooth 5.3
LAN	Intel® Ethernet Controller I225-V, 2.5G	Intel® Ethernet Controller I225-V, 2.5G
Audio	Realtek ALC269	Realtek ALC269
TPM	fTPM or TPM 2.0 chip	fTPM or TPM 2.0 chip
Card Reader	None	None .
HDMI CEC	Yes, 2 ports on back panel	Yes, 2 ports on back panel
Front I/O Ports	2 x USB 3.2 Gen2 Type-A 1 x 3.5mm Headset Jack	2 x USB 3.2 Gen2 Type-A 1 x 3.5mm Headset Jack
Back I/O Ports	2 x Thunderbolt 4 Type-C w/ DisplayPort 1.4 1 x USB 3.2 Gen 2 Type-A 1 x USB 2.0 Type-A 2 x HDMI 2.1 (TMDS) 1 x RJ45 LAN 1 x DC-in	2 x Thunderbolt 4 Type-C w/ DisplayPort 1.4 1 x USB 3.2 Gen 2 Type-A 1 x USB 2.0 Type-A 2 x HDMI 2.1 (TMDS) 1 x RJ45 LAN 1 x DC-in
Side I/O Ports	1 x Kensington Lock slot	1 x Kensington Lock slot
Power Supply	20VDC, 6.0A, 120W Power Adapter (i7/i5 CPU) 19VDC, 4.74A, 90W Power Adapter (i3 CPU)	20VDC, 6.0A, 120W Power Adapter (i7/i5 CPU) 19VDC, 4.74A, 90W Power Adapter (i3 CPU)
Operating Temp	0 to 40C	0 to 40C
Storage Temp	-20 to 40°C	-20 to 40°C
Humidity	0%-92% non-condensing <sup>1</sup>	0%-92% non-condensing <sup>1</sup>
Product Dimensions (W x D x H)	"H" 117 x 112 x 54 mm	"K" 117 x 112 x 37 mm
Product Weights	~610g	~502g
Color Box Dimensions (W x D x H)	"H" 193 x 171 x 122 mm	"K" 193 x 171 x 106 mm
Packaged Weights	~1.6 kg	~1.5 kg
Accessories	AC Adapter + Power Cord <sup>2</sup> VESA Bracket and Screws M3 Screws for 2.5in Drive Cable Clip Safety/Caution/Regulatory Insert Warranty Card	AC Adapter + Power Cord <sup>2</sup> VESA Bracket and Screws  Cable Clip  Safety/Caution/Regulatory Insert  Warranty Card

<sup>(1)</sup> Humidity Info detail please check link: Non-condensing Humidity defined by dew point.

 $<sup>{}^{(2)}\, \</sup>hbox{Power cord included is region specific, and some SKUs do not include the power cord.}$ 









**Kit Specifications** Image C Image D

it Specifications	· · · · · · · · · · · · · · · · · · ·	inage C inage D
Marketing Name	ASUS NUC 12 Pro Kit	ASUS NUC 12 Pro Kit
Project Code	NUC12WSH-B	NUC12WSK-B
Photo	Image C	Image D
ASUS Logo	N/A	N/A
•	N/A	N/A
ASUS NUC Logo	·	
Color	Black	Black
OS Support	Windows 11 64-bit	Windows 11 64-bit
	Windows 10 IoT Enterprise 64-bit	Windows 10 IoT Enterprise 64-bit
	RedHat Enterprise Linux 9.1 64-bit	RedHat Enterprise Linux 9.1 64-bit
	Ubuntu 20.04/22.04 LTS 64-bit	Ubuntu 20.04/22.04 LTS 64-bit
CPU	Intel® Core™ i7-1270P Processor w/ vPro, cTDP 40W	Intel® Core™ i7-1270P Processor w/ vPro, cTDP 40W
	Intel® Core™ i7-1260P Processor, cTDP 40W	Intel® Core™ i7-1260P Processor, cTDP 40W
	Intel® Core™ i5-1250P Processor w/ vPro, cTDP 40W	Intel® Core™ i5-1250P Processor w/ vPro, cTDP 40W
	Intel® Core™ i5-1240P Processor, cTDP 40W	Intel® Core™ i5-1240P Processor, cTDP 40W
	Intel® Core™ i3-1220P Processor, cTDP 15W	Intel® Core™ i3-1220P Processor, cTDP 15W
Chipset	Integrated	Integrated
•	Intel® Iris® Xe Graphics (i5/i7)	Intel® Iris® Xe Graphics (i5/i7)
Graphics	· · · · · · · ·	
	Intel® UHD Graphics (i3)	Intel® UHD Graphics (i3)
Memory	2 x SO-DIMM, Up to DDR4-3200, 32GB*2	2 x SO-DIMM, Up to DDR4-3200, 32GB*2
Storage		1 x M.2 2280 PCIe Gen4x4, supports 128GB~8TB NVMe SS
	1 x M.2 2280 PCIe Gen4x4, supports 128GB~8TB NVMe SSD	1 x M.2 2242 PCIe x1, supports SATA 128GB~1TB SATA SS
	1 x M.2 2242 PCle x1, supports SATA 128GB~1TB SATA SSD	1 x SATA Power/DATA header for 2.5in SSD/HDD, support
	1 x 2.5" SATA 6Gb/s, supports 4TB 7~15mm HDD	128GB~2TB SATA drive
Wireless Network	Intel® AX211 (Gig+), Wi-Fi 6E, Bluetooth 5.3	Intel® AX211 (Gig+), Wi-Fi 6E, Bluetooth 5.3
	Intel® vPro® Technology (i7/i5 vPro SKUs only)	Intel® vPro® Technology (i7/i5 vPro SKUs only)
LAN	Intel® Ethernet Controller I225-V/LM, 2.5G <sup>1</sup>	Intel® Ethernet Controller I225-V/LM, 2.5G <sup>1</sup>
Audio	Realtek ALC269	Realtek ALC269
TPM	fTPM or TPM 2.0 chip	fTPM or TPM 2.0 chip
Card Reader	None	None
HDMI CEC	Yes, 2 ports on back panel	Yes, 2 ports on back panel
Front I/O Ports	2 x USB 3.2 Gen2 Type-A	2 x USB 3.2 Gen2 Type-A
	1 x 3.5mm Headset Jack	1 x 3.5mm Headset Jack
Back I/O Ports	2 x Thunderbolt 4 Type-C w/ DisplayPort 1.4	2 x Thunderbolt 4 Type-C w/ DisplayPort 1.4
	1 x USB 3.2 Gen 2 Type-A	1 x USB 3.2 Gen 2 Type-A
	1 x USB 2.0 Type-A	1 x USB 2.0 Type-A
	2 x HDMI 2.0b	2 x HDMI 2.0b
	1 x RJ45 LAN	1 x RJ45 LAN
	1 x DC-in	1 x DC-in
Side I/O Ports	1 x Kensington Lock slot	1 x Kensington Lock slot
Power Supply	20VDC, 6.0A, 120W Power Adapter (i7/i5 CPU)	20VDC, 6.0A, 120W Power Adapter (i7/i5 CPU)
· cc. cappiy	19VDC, 4.74A, 90W Power Adapter (i3 CPU)	19VDC, 4.74A, 90W Power Adapter (i3 CPU)
Operating Temp	0 to 40°C	0 to 40°C
Storage Temp	-20 to 40°C	-20 to 40°C
	0%-92% non-condensing <sup>2</sup>	0%-92% non-condensing <sup>2</sup>
Humidity	0%-32% Horr-condensing-	0%-32% Hon-condensing-
Product Dimensions		
(W x D x H)	"H" 112 x 117 x 54 mm	"K" 112 x 171 x 106 mm
Product Weights	~612g	~512g
Color Box Dimensions	3	- 5
(W x D x H)	"H" 193 x 171 x 122 mm	"K" 193 x 171 x 106 mm
Packaged Weights	~1.6 kg	~1.5 kg
Accessories	AC Adapter + Power Cord <sup>3</sup>	дл с.1
Accessories	•	AC Adapter + Power Cord <sup>3</sup>
	VESA Bracket and Screws	VESA Bracket and Screws
	M3 Screws for 2.5in Drive	Cable Clip
	Cable Clip	Safety/Caution/Regulatory Insert
	Safety/Caution/Regulatory Insert	Warranty Card
	Warranty Card	Transity Cara

<sup>(1)</sup> Intel® Ethernet Controller 1225-LM included on vPro enabled systems
(2) Humidity Info detail please check link: Non-condensing Humidity defined by dew point.
(3) Power cord included is region specific, and some SKUs do not include the power cord





Image E



### **ASUS NUC 12 PRO**

### **Board Specifications**

Marketing Name	ASUS NUC 12 Pro Board
Project Code	NUC12WSB-M
Photo	Image E
ASUS Logo	N/A
ASUS NUC Logo	N/A
Color	N/A
OS Support	Windows 11 64-bit
	Windows 10 IoT Enterprise 64-bit
	RedHat Enterprise Linux 9.1 64-bit
	Ubuntu 20.04/22.04 LTS 64-bit

CPU

Intel® Core™ i7-1270P Processor w/ vPro, cTDP 40W

Intel® Core™ i7-1260P Processor, cTDP 40W

Intel® Core™ i5-1250P Processor w/ vPro, cTDP 40W

Intel® Core™ i5-1240P Processor, cTDP 40W

Intel® Core™ i3-1220P Processor, cTDP 15W

Chipset Integrated
Graphics Intel® Iris® Xe Graphics (i5/i7)

Intel® UHD Graphics (i3)

Memory 2 x SO-DIMM, Up to DDR4-3200, 32GB\*2

Storage 1 x M.2 2280 PCIe Gen4x4, supports 128GB~8TB NVMe SSD

1 x M.2 2242 PCIe x1, supports SATA 128GB~1TB SATA SSD

 $1\,x$  SATA Power/DATA header for 2.5in SSD/HDD, supports 128GB~2TB SATA drive

Wireless Network

LAN

Intel® Ethernet Controller 1225-V/LM, 2.5G¹

Audio

Realtek ALC269

TPM

fTPM or TPM 2.0 chip

Card Reader

None

HDMI CEC

Front I/O Ports

2 x USB 3.2 Gen2 Type-A
1 x 3.5mm Headset Jack

Back I/O Ports

2 x Thunderbolt 4 Type-C w/ DisplayPort 1.4

1 x USB 3.2 Gen 2 Type-A 1 x USB 2.0 Type-A 2 x HDMI 2.0b 1 x RJ45 LAN 1 x DC-in

Safety/Caution/Regulatory Insert

Side I/O Ports N/.

Power Supply 20VDC, 6.0A, 120W Power Adapter (i7/i5 CPU) 19VDC, 4.74A, 90W Power Adapter (i3 CPU)

Operating Temp0 to 50 °CStorage Temp-20 to 40 °CHumidity0%-92% non-condensing²

Product Dimensions

(W x D x H) 104.1mm x 101.6mm x 27mm

Product Weights ~1 kg

Color Box Dimensions

(W x D x H)

Packaged Weights

Accessories

232 x 155 x 135mm

71.5 kg

Warranty Card

(1) Intel® Ethernet Controller 1225-LM included on vPro enabled systems


<sup>(2)</sup> Humidity Info detail please check link: Non-condensing humidity defined by dew point.





Model NUC12WSH (Tall) Connections





- 2 x USB 3.2 Gen2 Type-A
- 2 1x 3.5mm Headset Jack
- 3 1x Power Bottom
- 4 1x 12-20 V DC Input Jack
- 5 1x Thunderbolt 4 Type-C w
- 6 2 x HDMI 2.0b
- 1x 2.5Gb Ethernet
- 8 1x USB 3.2 Gen 2, Type-A
- 9 1x USB 2.0, Type-A
- 10 1x Thunderbolt 4 Type-C w
- 11 1x Kensington Lock (Side Port)

### **Model NUCWSK (Slim) Connections**



- 1 2 x USB 3.2 Gen2 Type-A
- 2 1x 3.5mm Headset Jack
- 3 1x Power Bottom
- 4 1x12-20 V DC Input Jack
- 5 1x Thunderbolt 4 Type-C w
- 6 2 x HDMI 2.0b
- 7 1x 2.5Gb Ethernet
- 8 1x USB 3.2 Gen 2, Type-A
- 9 1x USB 2.0, Type-A
- 10 1x Thunderbolt 4 Type-C w
- 11 1x Kensington Lock (Side Port)






What's in the box







NUC 12 PRO



90 / 120 W power supply



Inserts



Power Cord\*



VESA bracket and Screws

#### NOTE:

- The most up-to-date and accurate product specifications are available on www.asus.com for download.
- · Product and accessory images are for illustrative purposes only. The actual appearance and specifications may vary depending on the model.
- \*The bundled power adapter may vary depending on the model and the country (or region) of sale.
- Some bundled accessories may vary depending on the model. For details on these accessories, refer to their respective user manuals.
- If the device or its components fail or malfunction during normal and proper use within the warranty period, bring the warranty card to the ASUS Service Center for replacement of the defective components.