

## ASUS MIL-STD 810H Test Report - B5604CM

| Test Category   | Test Method                    | MIL-STD-810H Test Parameters   | Test Result  |   |
|---|--------------------------------|--|--|---|
| Altitude Storage/<br>Air Transport                      | Method 500.6-Procedure I       | Test Pressure: Equivalent to cabin altitude of 40,000ft<br>Temperature: -20°C<br>Duration: 12 hour<br>Unit is non-operational during test.   | Pass   |   |
|   |                                | Altitude Operation/Air Carriage  |  | Test Pressure: Equivalent to cabin altitude of 15,000ft<br>Temperature: 5°C and 40°C<br>Duration: 12 hour (5°C) and 12 hour (40°C)<br>Unit is operational during test.  |
| High Temperature<br>Operational (Hot Dry)               | Method 501.7-Procedure II (A1) | Duration: 3 day exposure (3 X 24 hr. cycles)<br>Temperature: 32-49°C cycling temperature exposure<br>Table 501.7-III-Procedure. High temperature cycles, climate category A1 Hot Dry<br>Unit is operational during test.                         | Pass   |   |
|   |                                | High Temperature Storage and Transit (Hot Dry)   |  | Duration: 7 day exposure (7 X 24 hr. cycles)<br>Temperature: 33-71 °C cycling temperature exposure<br>Table 501.7-III-Procedure. High temperature cycles, climate category A1 Hot Dry<br>Unit is non-operational during test.                       |
| High Temperature<br>Operational (Basic Hot)             | Method 501.7-Procedure II (A2) | Duration: 3 day exposure (3 X 24 hr. cycles)<br>Temperature: 30-43°C cycling temperature exposure<br>Table 501.7-II-Procedure. High temperature cycles, climatic category A2 - Basic Hot<br>Humidity: 14-44%<br>Unit is operational during test. | Pass   |   |
|   |                                | High Temperature Storage and Transit (Basic Hot)   |  | Duration: 7 day exposure (7 X 24 hr. cycles)<br>Temperature: 30-63°C cycling temperature exposure<br>Table 501.7-II-Procedure. High temperature cycles, climatic category A2 - Basic Hot<br>Humidity: 5-44%<br>Unit is non-operational during test. |
| Low Temperature<br>Storage and Transit (Basic climatic) | Method 502.7- Procedure I (C1) | Duration: 7 day exposure (7 X 24 hr. cycles)<br>Temperature: -25- -33°C<br>Low temperature cycles, Table IX. Basic climatic_C1<br>Unit is non-operational during test.   | Pass   |   |
|   |                                | Low Temperature Operational (Basic climatic)   |  | Duration: 3 day exposure (3 X 24 hr. cycles)<br>Temperature: -21- -32°C<br>Low temperature cycles, Table IX. Basic climatic_C1<br>Unit is operational during test.  |
| Low Temperature<br>Storage and Transit (Cold climatic)  | Method 502.7- Procedure I (C2) | Duration: 7 day exposure (7 X 24 hr. cycles)<br>Temperature: -37- -46°C<br>Low temperature cycles, Table XI. Cold climatic_C2<br>Wind speed less than 5m/s(11mph)<br>Unit is non-operational during test.  | Pass   |   |
|   |                                | Low Temperature Operational (Cold climatic)  |  | Duration: 3 day exposure (3 X 24 hr. cycles)<br>Temperature: -37- -46°C<br>Low temperature cycles, Table XI. Cold climatic_C2<br>Wind speed less than 5m/s(11mph)<br>Unit is operational during test.   |
| Temperature Shock                                       | Method 503.7- Procedure I-C    | Duration: 1 Hour / Three cycles<br>Temperature: -51 to 71 °C<br>Unit is non-operational during test.   | Pass   |   |
| Sand and Dust   | Method 510.7- Procedure II     | Particle density: 1.1 +/- 0.3g/m <sup>3</sup><br>Air velocity: 28m/s<br>Operating temperature of 60 °C   | Pass   |   |
| Explosive Atmosphere                                    | Method 511.7- Procedure I      | Operation in an explosive atmosphere.  | Pass   |   |
|   | Vibration                      | Method 514.8- Procedure I (Table 514.8C-IV)  | Frequency 5-500Hz, Vertical rms = 3.98 g<br>Transverse rms = 1.22g, Longitudinal rms = 2.52g<br>Test Time: 32 minutes per axis | Pass  |
|   |                                | Method 514.8- Procedure I (Table 514.8C-VII)   | Frequency 5-500Hz, Vertical rms = 2.24 g<br>Transverse rms = 1.45g, Longitudinal rms = 1.32g<br>Test Time: 40 minutes per axis | Pass  |
|   | Method 516.8- Procedure I      | Functional Shock<br>Operational 3 shocks/axis/direction for a total of 18 shocks: 40 Gs peak, 11 ms  | Pass   |   |

|             |                             |  |      |
|-------------|-----------------------------|--|------|
| Shock       | Method 516.8- Procedure III | Non-operational 3 shocks/axis/direction for a total of 18 shocks<br>30-50 Gs peak, Trapezoidal pulse(772cm/s, 10G/each stage)        | Pass |
|             | Method 516.8- Procedure IV  | Transit Drop (Package)/122cm /26 Drop  | Pass |
|             | Method 516.8- Procedure V   | Crash Hazard Shock Test<br>2 shocks/axis/direction for a total of 12 shocks<br>75 Gs peak, 6 ms/Terminal Peak Sawtooth/unpackage nop | Pass |
|             | Method 516.8- Procedure VI  | Bench Handling<br>(Drop Height : 100 mm)<br>Unit is operational during test.   | Pass |
| Freeze/Thaw | Method 524.1- Procedure III | Rapid Temperature Change<br>Temperature: (30°C and -10°C)<br>Humidity: 95% RH<br>Dwell: 1Hour : Three cycles                         | Pass |

\*The testing regime includes the requirements of military-grade standards, and varies depending on device. MIL-STD-810 testing is conducted on selected ASUS products only. Note that the MIL-STD-810 testing helps to ensure the quality of ASUS products but does not indicate a particular fitness for military use. The test is performed under laboratory conditions. Any damage caused by attempts to replicate these test conditions would be considered accidental, and would not be covered by the standard ASUS warranty. Additional coverage is available with ASUS Premium Care.