

ASUS MIL-STD 810H Test Report - B5604CV

Test Category	Test Method	MIL-STD-810H Test Parameters	Test Result
Altitude Storage/ Air Transport	Method 500.6-Procedure I	Test Pressure: Equivalent to cabin altitude of 40,000ft	Pass
		Temperature: -20°C Duration: 12 hour Unit is non-operational during test.	
Altitude Operation/Air Carriage	Method 500.6-Procedure II	Test Pressure: Equivalent to cabin altitude of 15,000ft	Pass
		Temperature: 5°C and 40°C Duration: 12 hour (5°C) and 12 hour (40°C) Unit is operational during test.	
High Temperature Operational (Hot Dry)	Method 501.7-Procedure II (A1)	Duration: 3 day exposure (3 X 24 hr. cycles)	Pass
		Temperature: 32-49°C cycling temperature exposure Table 501.7-III-Procedure. High temperature cycles, climate category A1 Hot Dry Unit is operational during test.	
High Temperature Storage and Transit (Hot Dry)	Method 501.7-Procedure I (A1)	Duration: 7 day exposure (7 X 24 hr. cycles)	Pass
		Temperature: 33-71 °C cycling temperature exposure Table 501.7-III-Procedure. High temperature cycles, climate category A1 Hot Dry Unit is non-operational during test.	
High Temperature Storage and Transit (Basic Hot)	Method 501.7-Procedure I (A2)	Duration: 7 day exposure (7 X 24 hr. cycles)	Pass
		Temperature: 30-63°C cycling temperature exposure Table 501.7-II-Procedure. High temperature cycles, climatic category A2 - Basic Hot Humidity: 5-44% Unit is non-operational during test.	
Low Temperature Storage and Transit (Basic climatic)	Method 502.7- Procedure I (C1)	Duration: 7 day exposure (7 X 24 hr. cycles)	Pass
		Temperature: -25 - -33°C Low temperature cycles, Table IX. Basic climatic_C1 Unit is non-operational during test.	
Low Temperature Operational (Basic climatic)	Method 502.7- Procedure II (C1)	Duration: 3 day exposure (3 X 24 hr. cycles)	Pass
		Temperature: -21 - - 32°C Low temperature cycles, Table IX. Basic climatic_C1 Unit is operational during test.	
Low Temperature Storage and Transit (Cold climatic)	Method 502.7- Procedure I (C2)	Duration: 7 day exposure (7 X 24 hr. cycles)	Pass
		Temperature: -37 - -46°C Low temperature cycles, Table XI. Cold climatic_C2 Wind speed less than 5m/s(11mph) Unit is non-operational during test.	
Temperature Shock	Method 503.7- Procedure I-C	Duration: 1 Hour / Three cycles Temperature: -51 to 71 °C Unit is non-operational during test.	Pass
Explosive Atmosphere	Method 511.7- Procedure I	Operation in an explosive atmosphere.	Pass
Vibration	Method 514.8- Procedure I (Table 514.8C-I)	Frequency 5-500Hz, Vertical rms = 1.08 g Transverse rms = 0.21g, Longitudinal rms = 0.76g Test Time: 60 minutes per axis (US highway truck vibration exposure)	Pass
	Method 514.8- Procedure I (Table 514.8C-IV)	Frequency 5-500Hz, Vertical rms = 3.98 g Transverse rms = 1.22g, Longitudinal rms = 2.52g Test Time: 32 minutes per axis	Pass
	Method 514.8- Procedure I (Table 514.8C-VII)	Frequency 5-500Hz, Vertical rms = 2.24 g Transverse rms = 1.45g, Longitudinal rms = 1.32g Test Time: 40 minutes per axis	Pass
Shock	Method 516.8- Procedure I	Functional Shock Operational 3 shocks/axis/direction for a total of 18 shocks: 40 Gs peak, 11 ms	Pass
	Method 516.8- Procedure III	Fragility Non-operational 3 shocks/axis/direction for a total of 18 shocks 30-50 Gs peak, Trapezoidal pulse(772cm/s, 10G/each stage)	Pass
	Method 516.8- Procedure IV	Transit Drop (Package)/122cm /26 Drop	Pass
	Method 516.8- Procedure V	Crash Hazard Shock Test 2 shocks/axis/direction for a total of 12 shocks 75 Gs peak, 6 ms/Terminal Peak Sawtooth/unpackage nop	Pass
	Method 516.8- Procedure VI	Bench Handling (Drop Height : 100 mm) Unit is operational during test.	Pass
		Rapid Temperature Change	

Freeze/Thaw	Method 524.1- Procedure III	Temperature: (30°C and -10°C) Humidity: 95% RH Dwell: 1Hour : Three cycles	Pass
Mechanical Vibrations of Shipboard Equipment	Method 528.1- Procedure1 (Type 1)	Environmental Vibration 4-33 Hz/ 2Hours	Pass

*The testing regime includes the requirements of military-grade standards, and varies depending on device. MIL-STD-810 testing is conducted on selected ASUS products only. Note that the MIL-STD-810 testing helps to ensure the quality of ASUS products but does not indicate a particular fitness for military use. The test is performed under laboratory conditions. Any damage caused by attempts to replicate these test conditions would be considered accidental, and would not be covered by the standard ASUS warranty. Additional coverage is available with ASUS Premium Care.