

ASUS MIL-STD 810H Test Report - D700SER

| Test Category | Test Method | MIL-STD-810H Test Parameters | Test Result |
|---|---|---|-------------|
| Altitude Storage/ Air Transport | Method 500.6-Procedure I | Test Pressure: Equivalent to cabin altitude of 40,000ft Temperature: -20°C Duration: 12 hour Unit is non-operational during test. | Pass |
| Altitude Operation/Air Carriage | Method 500.6-Procedure II | Test Pressure: Equivalent to cabin altitude of 15,000ft Temperature: 5°C and 40°C Duration: 12 hour (5°C) and 12 hour (40°C) Unit is operational during test. | Pass |
| High Temperature Operational (Hot Dry) | Method 501.7-Procedure II (A1) | Duration: 3 day exposure (3 X 24 hr. cycles) Temperature: 32-49°C cycling temperature exposure Table 501.7-III-Procedure. High temperature cycles, climate category A1 Hot Dry Unit is operational during test. | Pass |
| High Temperature Storage and Transit (Hot Dry) | Method 501.7-Procedure I (A1) | Duration: 7 day exposure (7 X 24 hr. cycles) Temperature: 33-71°C cycling temperature exposure Table 501.7-III-Procedure. High temperature cycles, climate category A1 Hot Dry Unit is non-operational during test. | Pass |
| High Temperature Operational (Basic Hot) | Method 501.7-Procedure II (A2) | Duration: 3 day exposure (3 X 24 hr. cycles) Temperature: 30-43°C cycling temperature exposure Table 501.7-II-Procedure. High temperature cycles, climatic category A2 - Basic Hot Humidity: 14-44% Unit is operational during test. | Pass |
| High Temperature Storage and Transit (Basic Hot) | Method 501.7-Procedure I (A2) | Duration: 7 day exposure (7 X 24 hr. cycles) Temperature: 30-63°C cycling temperature exposure Table 501.7-II-Procedure. High temperature cycles, climatic category A2 - Basic Hot Humidity: 5-44% Unit is non-operational during test. | Pass |
| Low Temperature Storage and Transit (Basic climatic) | Method 502.7- Procedure I (C1) | Duration: 7 day exposure (7 X 24 hr. cycles) Temperature: -25~ -33°C Low temperature cycles, Table IX. Basic climatic_C1 Unit is non-operational during test. | Pass |
| Low Temperature Operational (Basic climatic) | Method 502.7- Procedure II (C1) | Duration: 3 day exposure (3 X 24 hr. cycles) Temperature: -21 ~ -32°C Low temperature cycles, Table IX. Basic climatic_C1 Unit is operational during test. | Pass |
| Low Temperature Storage and Transit (Cold climatic) | Method 502.7- Procedure I (C2) | Duration: 7 day exposure (7 X 24 hr. cycles) Temperature: -37 ~ -46°C Low temperature cycles, Table XI. Cold climatic_C2 Wind speed less than 5m/s(11mph) Unit is non-operational during test. | Pass |
| Low Temperature Operational (Cold climatic) | Method 502.7- Procedure II (C2) | Duration: 3 day exposure (3 X 24 hr. cycles) Temperature: -37 ~ -46°C Low temperature cycles, Table XI. Cold climatic_C2 Wind speed less than 5m/s(11mph) Unit is operational during test. | Pass |
| Temperature Shock | Method 503.7- Procedure I-C | Duration: 1 Hour / Three cycles Temperature: -51 to 71 °C Unit is non-operational during test. | Pass |
| Humidity Aggravated Cycle | Method 507.6- Procedure II | Duration: 10 Days Temperature: 30°C and 60°C Humidity: 95% RH, constant Unit is non-operational during test. | Pass |
| Vibration | Method 514.8- Procedure I (Table 514.8C-IV) | Frequency 5-500Hz, Vertical rms = 3.98 g Transverse rms = 1.22g, Longitudinal rms = 2.52g Test Time: 32 minutes per axis | Pass |
| | Method 514.8- Procedure I (Table 514.8C-VII) | Frequency 5-500Hz, Vertical rms = 2.24 g Transverse rms = 1.45g, Longitudinal rms = 1.32g Test Time: 40 minutes per axis | Pass |
| Shock | Method 516.8- Procedure I | Functional Shock Operational 3 shocks/axis/direction for a total of 18 shocks; 40 Gs peak, 11 ms Transportation shock- On road (5000Km) | Pass |
| | Method 516.8- Procedure II | Amplitude : 5.1 ~ 7.6 G-Pk , Number of Shocks: 3 ~ 42 times Pulse Duration: 11ms Terminal Peak Sawtooth Non-OP/ Package | Pass |

Freeze/Thaw

Method 524.1- Procedure III

Rapid Temperature Change
Temperature: (30°C and -10°C)
Humidity: 95% RH
Dwell: 1Hour : Three cycles

Pass

*The testing regime includes the requirements of military-grade standards, and varies depending on device. MIL-STD-810 testing is conducted on selected ASUS products only. Note that the MIL-STD-810 testing helps to ensure the quality of ASUS products but does not indicate a particular fitness for military use. The test is performed under laboratory conditions. Any damage caused by attempts to replicate these test conditions would be considered accidental, and would not be covered by the standard ASUS warranty. Additional coverage is available with ASUS Premium Care.