

# ASUS Desktop D901SDR MIL-STD 810H Test Report

Test Category	Test Method	MIL-STD-810H Test Parameters	Test Result
Altitude Storage/ Air Transport	Method 500.6-Procedure I	Test Pressure: Equivalent to cabin altitude of 40,000ft Temperature: -20°C Duration: 12 hour Unit is non-operational during test.	Pass
Altitude Operation/Air Carriage	Method 500.6-Procedure II	Test Pressure: Equivalent to cabin altitude of 15,000ft Temperature: 5°C and 40°C Duration: 12 hour (5°C) and 12 hour (40°C) Unit is operational during test.	Pass
High Temperature Operational (Hot Dry)	Method 501.7-Procedure II (A1)	Duration: 3 day exposure (3 X 24 hr. cycles) Temperature: 32-49°C cycling temperature exposure Table 501.7-III-Procedure. High temperature cycles, climate category A1 Hot Dry Unit is operational during test.	Pass
High Temperature Storage and Transit (Hot Dry)	Method 501.7-Procedure I (A1)	Duration: 7 day exposure (7 X 24 hr. cycles) Temperature: 33-71°C cycling temperature exposure Table 501.7-III-Procedure. High temperature cycles, climate category A1 Hot Dry Unit is non-operational during test.	Pass
High Temperature Operational (Basic Hot)	Method 501.7-Procedure II (A2)	Duration: 3 day exposure (3 X 24 hr. cycles) Temperature: 30-43°C cycling temperature exposure Table 501.7-II-Procedure. High temperature cycles, climatic category A2 - Basic Hot Humidity: 14-44% Unit is operational during test.	Pass
High Temperature Storage and Transit (Basic Hot)	Method 501.7-Procedure I (A2)	Duration: 7 day exposure (7 X 24 hr. cycles) Temperature: 30-63°C cycling temperature exposure Table 501.7-II-Procedure. High temperature cycles, climatic category A2 - Basic Hot Humidity: 5-44% Unit is non-operational during test.	Pass
Low Temperature Storage and Transit (Basic climatic)	Method 502.7- Procedure I (C1)	Duration: 7 day exposure (7 X 24 hr. cycles) Temperature: -25 - -33°C Low temperature cycles, Table IX. Basic climatic_C1 Unit is non-operational during test.	Pass
Low Temperature Operational (Basic climatic)	Method 502.7- Procedure II (C1)	Duration: 3 day exposure (3 X 24 hr. cycles) Temperature: -21 - -32°C Low temperature cycles, Table IX. Basic climatic_C1 Unit is operational during test.	Pass
Low Temperature Storage and Transit (Cold climatic)	Method 502.7- Procedure I (C2)	Duration: 7 day exposure (7 X 24 hr. cycles) Temperature: -37 - -46°C Low temperature cycles, Table XI. Cold climatic_C2 Wind speed less than 5m/s(11mph) Unit is non-operational during test.	Pass
Low Temperature Operational (Cold climatic)	Method 502.7- Procedure II (C2)	Duration: 3 day exposure (3 X 24 hr. cycles) Temperature: -37 - -46°C Low temperature cycles, Table XI. Cold climatic_C2 Wind speed less than 5m/s(11mph) Unit is operational during test.	Pass
Temperature Shock	Method 503.7- Procedure I-C	Duration: 1 Hour / Three cycles Temperature: -51 to 71 °C Unit is non-operational during test.	Pass
Humidity Aggravated Cycle	Method 507.6- Procedure II	Duration: 10 Days Temperature: 30°C and 60°C Humidity: 95% RH, constant Unit is non-operational during test.	Pass
Vibration	Method 514.8- Procedure I (Table 514.8C-VII)	Frequency 5-500Hz, Vertical rms = 2.24 g Transverse rms = 1.45g, Longitudinal rms = 1.32g Test Time: 40 minutes per axis	Pass
Shock	Method 516.8- Procedure I	Functional Shock Operational 3 shocks/axis/direction for a total of 18 shocks: 40 Gs peak, 11 ms Transportation shock- On road (5000Km)	Pass
	Method 516.8- Procedure II	Amplitude : 5.1 - 7.6 G-Pk , Number of Shocks: 3 - 42 times Pulse Duration: 11ms	Pass

		Terminal Peak Sawtooth Non-OP/ Package	
	Method 516.8- Procedure IV	Transit Drop (Package)/122cm /26 Drop	Pass
Freeze/Thaw	Method 524.1- Procedure III	Rapid Temperature Change Temperature: (30°C and -10°C) Humidity: 95% RH Dwell: 1Hour : Three cycles	Pass

\*The testing regime includes the requirements of military-grade standards, and varies depending on device. MIL-STD-810 testing is conducted on selected ASUS products only. Note that the MIL-STD-810 testing helps to ensure the quality of ASUS products but does not indicate a particular fitness for military use. The test is performed under laboratory conditions. Any damage caused by attempts to replicate these test conditions would be considered accidental, and would not be covered by the standard ASUS warranty. Additional coverage is available with ASUS Premium Care.